



(317) 346-4110

www.drainagesolutionsinc.com

CenFlo HDPE

HDPE 3608 — ASTM D2239

- Flexible polyethylene pipe and tubing
- Produced from only the finest virgin material
- Backed by a **30-YEAR WARRANTY**
- Virgin Black material

ASTM D2239			1/2"	3/4"	1"	1-1/4"	1-1/2"	2"
80 PSI	SIDR 19	O.D.	N/A	N/A	1.169"	1.526"	1.810"	2.285"
		I.D.	N/A	N/A	1.049"	1.380"	1.610"	2.067"
		Wall	N/A	N/A	.060"	.073"	.100"	.109"
		Wt/ft	N/A	N/A	.093#	.148#	.231#	.324#
		Coil Lengths	N/A	N/A	100-300 ft.	100-300 ft.	100-250 ft.	100-200 ft.

100 PSI	SIDR 15	O.D.	N/A	.944"	1.189"	1.564"	1.824"	2.343"
		I.D.	N/A	.824"	1.049"	1.380"	1.610"	2.067"
		Wall	N/A	.060"	.070"	.092"	.107"	.138"
		Wt/Ft	N/A	.074#	.109#	.187#	.251#	.416#
		Coil Lengths	N/A	100-400 ft.	100-300 ft.	100-300 ft.	100-250 ft.	100-200 ft.

Note: CenFlo HDPE SIDR 19 and SIDR 15 are suitable for connections with insert fittings and clamps.



Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.