



Equipped with (2) 300SS Clamps  
Installation Torque 60 in-lb



Part Weight	3.33 lbs.
Min/Max Temp.	-30/140 Degrees F
Pressure Tested	4.3 PSI
Material	Flexible PVC 60 Duro Shore A
Installation Torque	60" Lbs.
Conforms to ASTM	D5926, C1173
Box Quantity	20
Clamps used	300 Series

TOLERANCES:  
.X= Fractional ±  
.XX= ±.060  
.XXX= ±.032  
ANG.= ±0.5°  
UNLESS OTHERWISE SPECIFIED

DESCRIPTION:  
**Coupling 6" Clay x 4" Clay**

**1001-64**

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FERNCO, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FERNCO, INC. IS PROHIBITED.

UNITS: <b>INCHES</b>	SIZE <b>A</b>	DESIGNER: <b>AJD</b>	SCALE not to scale
3RD ANGLE PROJECTION DO NOT SCALE DRAWING		CHECKER:	DATE: <b>10/17/2014</b> SHEET 1 OF 1