

REV	DATE	REVISION DESCRIPTION
A	8-26-05	ALTERED B.C.D. ON DRILL POINTS TO 24.25
B	5-31-07	ADDED NOTES, BOLT PACK

.25 DIA. THRU ON 24.75 B.C.D.
WITH COUNTERSINK (4) PLACES

(4) DRILL POINTS ON 24.250 BCD FOR
ADDITIONAL SCREWS IF REQUIRED.

8X3/8 SS PAN HEAD
SCREWS (4 PLACES)

SFRC24SEAL(PVC)

R11.313 (4)

Ø22.875

.313
TYP

1.500
-1.000

Ø26.500

DO NOT ENTER WITHOUT PROPER EQUIPMENT
DANGEROUS GASES EXIST IN TANK

DO NOT ENTER WITHOUT PROPER EQUIPMENT
DANGEROUS GASES EXIST IN TANK


WWW.JACKELINC.COM
PATENT PENDING
JACKEL INC.
PART NO. SFRC24
Tech-Tough

OPTIONAL CUSTOMIZED NAMEPLATE
ATTACHED WITH 6x5/16 S.S.
U-DRIVE SCREWS

(4) .31 DIA. HOLES THRU SEAL
CLEARANCE FOR SCREWS IF ADDITIONAL
HOLES ARE USED (OPPOSITE DRILL POINTS)

1.00 (4)

(4) 12x2 S.S. FLAT HEAD
SQUARE DRIVE MOUNTING SCREWS
IN POLYBAG ATTACHED TO
COVER WITH U-DRIVE SCREW



NOTES:

1. INSTALL WITH SCREWS PROVIDED.
2. DRILL POINTS FOR ADDITIONAL SCREWS PROVIDED IF REQUIRED.
3. IF RISER IS NOT CUT SMOOTHLY OR UNIFORMLY ACROSS ITS DIAMETER, ADDITIONAL GASKETING MATERIAL OR CAULKING MAY BE REQUIRED.

JACKEL, INC.

PART NAME

SFRC24-GR, SFRC24-BL

MATERIAL

STRUCTURAL FOAM HDPE

FINISH

GREEN OR BLACK, AS MOLDED

UNITS

INCHES

TOLERANCE

NA

SCALE

NA

REVISED

5-31-07

CHECKED BY

J. HASLOCK

DRAWN BY

S. JACKMAN

SHEET

1

OF

1

DATE

5-31-07



(317) 346-4110

www.drainagesolutionsinc.com

DRAINAGE SOLUTIONS, INC