

## PRODUCT DATA SHEET

## **WINFAB 200W**





**WINFAB 200W** is manufactured using high tenacity polypropylene yarns that are woven to form a dimensionally stable network, which allows the yarns to maintain their relative position.

**WINFAB 200W** resists ultraviolet deterioration, rotting, and biological degradation and is inert to commonly encountered soil chemicals.

| PROPERTY                     | TEST METHOD | MARV English           | MARV Metric            |
|------------------------------|-------------|------------------------|------------------------|
| Tensile Strength (Grab)      | ASTM D-4632 | 200 x 200 lbs          | 890 x 890 N            |
| Elongation                   | ASTM D-4632 | 15%                    | 15%                    |
| CBR Puncture                 | ASTM D-6241 | 700 lbs                | 3114 N                 |
| Trapezoidal Tear             | ASTM D-4533 | 75 x 75 lbs            | 330 x 330 N            |
| UV Resistance (500 hrs)      | ASTM D-4355 | 70%                    | 70%                    |
| Apparent Opening Size (AOS)* | ASTM D-4751 | 40 US Std. Sieve       | 0.425 mm               |
| Permittivity                 | ASTM D-4491 | 0.05 sec <sup>-1</sup> | 0.05 sec <sup>-1</sup> |
| Water Flow Rate              | ASTM D-4491 | 5 gpm/ft <sup>2</sup>  | 204 lpm/m <sup>2</sup> |

<sup>\*</sup>Maximum Average Roll Valve

## Notes:

- Mullen Burst ASTM D-3786 has been removed. It is not recognized by ASTM D-35 on Geosynthetics.
- Puncture ASTM D-4833 has been removed. It is not recognized by AASHTO M288 and has been replaced with CBR Puncture ASTM D-6241

| PROPERTY        | Typical English     | Typical Metric     |
|-----------------|---------------------|--------------------|
| Roll Dimensions | 12.5 x 432 ft       | 3.81 x 131.7 m     |
|                 | 15 x 360 ft         | 4.6 x 109.7 m      |
|                 | 17.5 x 309 ft       | 5.3 x 94.2 m       |
| Roll Area       | 600 yd <sup>2</sup> | 502 m <sup>2</sup> |

**Disclaimer:** Willacoochee Industrial Fabrics assumes no liability for the completeness or accuracy of this information or the ultimate use of this information. Willacoochee Industrial Fabrics disclaims any and all implied, expressed, or statutory standards, guarantees, or warranties. This includes without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to equipment, materials, or information furnished herewith. This document should not be construed as engineering advice. Always consult the project engineer for project specific requirements. The end user assumes sole responsibility for the use of this information and product. The property values listed above are subject to change without notice.

© 2013 Willacoochee Industrial Fabrics, Inc.



